

Python For Data Science Cheat Sheet

Pandas Basics

Learn Python for Data Science Interactively at www.DataCamp.com



Pandas

The Pandas library is built on NumPy and provides easy-to-use data structures and data analysis tools for the Python programming language.




Use the following import convention:

```
>>> import pandas as pd
```

Pandas Data Structures

Series

A one-dimensional labeled array capable of holding any data type



```
>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])
```

DataFrame

Columns

	Country	Capital	Population
0	Belgium	Brussels	11190846
1	India	New Delhi	1303171035
2	Brazil	Brasilia	207847528

Index

A two-dimensional labeled data structure with columns of potentially different types

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
           'Capital': ['Brussels', 'New Delhi', 'Brasilia'],
           'Population': [11190846, 1303171035, 207847528]}

>>> df = pd.DataFrame(data,
                      columns=['Country', 'Capital', 'Population'])
```

I/O

Read and Write to CSV

```
>>> pd.read_csv('file.csv', header=None, nrows=5)
>>> df.to_csv('myDataFrame.csv')
```

Read and Write to Excel

```
>>> pd.read_excel('file.xlsx')
>>> pd.to_excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')

Read multiple sheets from the same file
>>> xlsx = pd.ExcelFile('file.xls')
>>> df = pd.read_excel(xlsx, 'Sheet1')
```

Asking For Help

```
>>> help(pd.Series.loc)
```

Selection

Also see NumPy Arrays

Getting

```
>>> s['b']
-5
Get one element

>>> df[1:]
Country Capital Population
1 India New Delhi 1303171035
2 Brazil Brasilia 207847528
Get subset of a DataFrame
```

Selecting, Boolean Indexing & Setting

By Position

```
>>> df.iloc[[0],[0]]
'Belgium'
Select single value by row & column

>>> df.iat([0],[0])
'Belgium'
```

By Label

```
>>> df.loc[[0], ['Country']]
'Belgium'
Select single value by row & column labels

>>> df.at([0], ['Country'])
'Belgium'
```

By Label/Position

```
>>> df.ix[2]
Country Brazil
Capital Brasilia
Population 207847528
Select single row of subset of rows
```

```
>>> df.ix[:, 'Capital']
0 Brussels
1 New Delhi
2 Brasilia
Select a single column of subset of columns
```

```
>>> df.ix[1, 'Capital']
'New Delhi'
Select rows and columns
```

Boolean Indexing

```
>>> s[~(s > 1)]
Series s where value is not > 1
>>> s[(s < -1) | (s > 2)]
s where value is <-1 or >2
>>> df[df['Population'] > 1200000000]
Use filter to adjust DataFrame
```

Setting

```
>>> s['a'] = 6
Set index a of Series s to 6
```

Dropping

```
>>> s.drop(['a', 'c'])
Drop values from rows (axis=0)
>>> df.drop('Country', axis=1)
Drop values from columns(axis=1)
```

Sort & Rank

```
>>> df.sort_index()
Sort by labels along an axis
>>> df.sort_values(by='Country')
Sort by the values along an axis
>>> df.rank()
Assign ranks to entries
```

Retrieving Series/DataFrame Information

Basic Information

```
>>> df.shape
(rows,columns)
>>> df.index
Describe index
>>> df.columns
Describe DataFrame columns
>>> df.info()
Info on DataFrame
>>> df.count()
Number of non-NA values
```

Summary

```
>>> df.sum()
Sum of values
>>> df.cumsum()
Cumulative sum of values
>>> df.min()/df.max()
Minimum/maximum values
>>> df.idxmin()/df.idxmax()
Minimum/Maximum index value
>>> df.describe()
Summary statistics
>>> df.mean()
Mean of values
>>> df.median()
Median of values
```

Applying Functions

```
>>> f = lambda x: x*2
>>> df.apply(f)
Apply function
>>> df.applymap(f)
Apply function element-wise
```

Data Alignment

Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
a 10.0
b NaN
c 5.0
d 7.0
```

Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill_value=0)
a 10.0
b -5.0
c 5.0
d 7.0
>>> s.sub(s3, fill_value=2)
>>> s.div(s3, fill_value=4)
>>> s.mul(s3, fill_value=3)
```

Read and Write to SQL Query or Database Table

```
>>> from sqlalchemy import create_engine
>>> engine = create_engine('sqlite:///memory:')
>>> pd.read_sql("SELECT * FROM my_table;", engine)
>>> pd.read_sql_table('my_table', engine)
>>> pd.read_sql_query("SELECT * FROM my_table;", engine)

read_sql() is a convenience wrapper around read_sql_table() and
read_sql_query()

>>> pd.to_sql('myDf', engine)
```



Python For Data Science Cheat Sheet

Pandas

Learn Python for Data Science Interactively at www.DataCamp.com



Reshaping Data

Pivot

```
>>> df3= df2.pivot(index='Date',
                    columns='Type',
                    values='Value')
```

Spread rows into columns

Date	Type	Value
2016-03-01	a	11.432
2016-03-02	b	13.031
2016-03-01	c	20.784
2016-03-03	a	99.906
2016-03-02	a	1.303
2016-03-03	c	20.784

Type	a	b	c
Date			
2016-03-01	11.432	NaN	20.784
2016-03-02	1.303	13.031	NaN
2016-03-03	99.906	NaN	20.784

Pivot Table

```
>>> df4 = pd.pivot_table(df2,
                          values='Value',
                          index='Date',
                          columns='Type')
```

Spread rows into columns

Stack / Unstack

```
>>> stacked = df5.stack()
>>> stacked.unstack()
```

Pivot a level of column labels
Pivot a level of index labels

	0	1
1	0.233482	0.390959
2	0.184713	0.237102
3	0.433522	0.429401

Unstacked

	0	1
1	0.233482	0.390959
2	0.184713	0.237102
3	0.433522	0.429401

Stacked

Melt

```
>>> pd.melt(df2,
            id_vars=["Date"],
            value_vars=["Type", "Value"],
            value_name="Observations")
```

Gather columns into rows

Date	Type	Value
2016-03-01	a	11.432
2016-03-02	b	13.031
2016-03-01	c	20.784
2016-03-03	a	99.906
2016-03-02	a	1.303
2016-03-03	c	20.784

Date	Variable	Observations
2016-03-01	Type	a
2016-03-02	Type	b
2016-03-01	Type	c
2016-03-03	Type	a
2016-03-02	Type	a
2016-03-03	Type	c
2016-03-01	Value	11.432
2016-03-02	Value	13.031
2016-03-01	Value	20.784
2016-03-03	Value	99.906
2016-03-02	Value	1.303
2016-03-03	Value	20.784

Iteration

```
>>> df.iteritems()
>>> df.iterrows()
```

(Column-index, Series) pairs
(Row-index, Series) pairs

Advanced Indexing

Also see NumPy Arrays

Selecting

```
>>> df3.loc[:, (df3>1).any()]
>>> df3.loc[:, (df3>1).all()]
>>> df3.loc[:, df3.isnull().any()]
>>> df3.loc[:, df3.notnull().all()]
```

Select cols with any vals >1
Select cols with vals > 1
Select cols with NaN
Select cols without NaN

Indexing With isin

```
>>> df[(df.Country.isin(df2.Type))]
>>> df3.filter(items=["a", "b"])
>>> df.select(lambda x: not x%5)
```

Find same elements
Filter on values
Select specific elements

Where

```
>>> s.where(s > 0)
```

Subset the data

Query

```
>>> df6.query('second > first')
```

Query DataFrame

Setting/Resetting Index

```
>>> df.set_index('Country')
>>> df4 = df.reset_index()
>>> df = df.rename(index=str,
                  columns={"Country": "cntry",
                           "Capital": "cptl",
                           "Population": "ppltn"})
```

Set the index
Reset the index
Rename DataFrame

Reindexing

```
>>> s2 = s.reindex(['a', 'c', 'd', 'e', 'b'])
```

Forward Filling

```
>>> df.reindex(range(4),
               method='ffill')
```

Country	Capital	Population
0	Belgium	Brussels
1	India	New Delhi
2	Brazil	Brasilia
3	Brazil	Brasilia

Backward Filling

```
>>> s3 = s.reindex(range(5),
                   method='bfill')
```

0	3
1	3
2	3
3	3
4	3

MultiIndexing

```
>>> arrays = [np.array([1,2,3]),
              np.array([5,4,3])]
>>> df5 = pd.DataFrame(np.random.rand(3, 2), index=arrays)
>>> tuples = list(zip(*arrays))
>>> index = pd.MultiIndex.from_tuples(tuples,
                                    names=['first', 'second'])
>>> df6 = pd.DataFrame(np.random.rand(3, 2), index=index)
>>> df2.set_index(["Date", "Type"])
```

Duplicate Data

```
>>> s3.unique()
>>> df2.duplicated('Type')
>>> df2.drop_duplicates('Type', keep='last')
>>> df.index.duplicated()
```

Return unique values
Check duplicates
Drop duplicates
Check index duplicates

Grouping Data

Aggregation

```
>>> df2.groupby(by=['Date', 'Type']).mean()
>>> df4.groupby(level=0).sum()
>>> df4.groupby(level=0).agg({'a': lambda x: sum(x)/len(x),
                             'b': np.sum})
```

Transformation

```
>>> customSum = lambda x: (x+x%2)
>>> df4.groupby(level=0).transform(customSum)
```

Missing Data

```
>>> df.dropna()
>>> df3.fillna(df3.mean())
>>> df2.replace("a", "f")
```

Drop NaN values
Fill NaN values with a predetermined value
Replace values with others

Combining Data

data1		data2	
X1	X2	X1	X3
a	11.432	a	20.784
b	1.303	b	NaN
c	99.906	d	20.784

Merge

```
>>> pd.merge(data1,
             data2,
             how='left',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
c	99.906	NaN

```
>>> pd.merge(data1,
             data2,
             how='right',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
d	NaN	20.784

```
>>> pd.merge(data1,
             data2,
             how='inner',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN

```
>>> pd.merge(data1,
             data2,
             how='outer',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
c	99.906	NaN
d	NaN	20.784

Join

```
>>> data1.join(data2, how='right')
```

Concatenate

Vertical

```
>>> s.append(s2)
>>> pd.concat([s, s2], axis=1, keys=['One', 'Two'])
```

Horizontal/Vertical

```
>>> pd.concat([data1, data2], axis=1, join='inner')
```

Dates


```
>>> df2['Date'] = pd.to_datetime(df2['Date'])
>>> df2['Date'] = pd.date_range('2000-1-1',
                              periods=6,
                              freq='M')
>>> dates = [datetime(2012, 5, 1), datetime(2012, 5, 2)]
>>> index = pd.DatetimeIndex(dates)
>>> index = pd.date_range(datetime(2012, 2, 1), end, freq='BM')
```

Visualization

Also see Matplotlib

```
>>> import matplotlib.pyplot as plt
```

```
>>> s.plot()
>>> plt.show()
```



```
>>> df2.plot()
>>> plt.show()
```

